

EAST - [Untitled1:1]

File View Edit Tools Window Help

Drafts

- ISNR:
- BRS:
- BRS:
- ISNR:
- BRS: WITH

Pending

Active

- L1: (520) (49/475.1).CCLS.
- L2: (595) (49/490.1).CCLS.
- L3: (537) (49/498.1).CCLS.
- L4: (244) (277/419).CCLS.
- L5: (46) (weatherseal or (weather adj s
- L6: (1198) seal same light same (illumina
- L7: (315) seal with light with (illumina

Failed

- (0) ("49/49.ccls. and "red light" and "
- (0) ((weatherseal or (weather adj seal)

Saved

Submit Edit Browse Queue Clear

DBs USPAT EPO JPO DERWENT IBM TDB

Plurals

Default operator: OR

Highlight all hit terms initially

seal with light with (illuminat\$ or bright\$)

BRS term CAR term Image Text HTML

| | U | 1 | Document ID | Current OR | Image Doc. Dis | PT |
|---|--------------------------|-------------------------------------|-------------|------------|----------------|--------------------------|
| 1 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5799124 | 385/125 | US 5799124 | <input type="checkbox"/> |
| 2 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5604999 | 36/137 | US 5604999 | <input type="checkbox"/> |
| 3 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | DE 3843386 | | DE 3843386 A1 | <input type="checkbox"/> |
| 4 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | WO 9005924 | | WO 9005924 A1 | <input type="checkbox"/> |
| 5 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | EP 871320 A | | US 5872355 | <input type="checkbox"/> |
| 6 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 4751434 | | US 4751434 | <input type="checkbox"/> |

BRS search 7/8/02

Hit Details HTML

Ready

NUM

CLIPPEDIMAGE= DE003843386A1

PUB-NO: DE003843386A1

DOCUMENT-IDENTIFIER: DE 3843386 A1

TITLE: Front-loading drum-type washing machine

PUBN-DATE: July 5, 1990

INVENTOR-INFORMATION:

NAME

COUNTRY

GUTE, KLAUS ING GRAD

DE

KRIMPHOFF, PAUL

DE

ASSIGNEE-INFORMATION:

NAME

COUNTRY

LICENTIA GMBH

DE

APPL-NO: DE03843386

APPL-DATE: December 23, 1988

PRIORITY-DATA: DE03843386A (December 23, 1988)

INT-CL (IPC): D06F037/02

EUR-CL (EPC): D06F037/00; D06F037/26, D06F039/12

US-CL-CURRENT: 68/13R

ABSTRACT:

Front-loading drum-type washing machine with an electrical [REDACTED] source (9) for [REDACTED] the laundry-drum interior (11), in which the laundry drum (7) is arranged rotatably in a tub (5) and a concertina-type [REDACTED] (8) extends between the machine housing (1, 2) and the tub (5) around the loading orifice (3). The loading orifice (3) is closed by a pot-like bull's eye door window (4, 4') extending as far as the laundry drum (7). The electrical light source (9) is provided outside the tub (5). The light source (9) is assigned a light guide (10) which is guided through the concertina-type seal (8) and which is directed with its light-exit region (12) towards the inside of the laundry-drum rear wall. <IMAGE>

CLIPPEDIMAGE= WO009005924A1
PUB-NO: WO009005924A1
DOCUMENT-IDENTIFIER: WO 9005924 A1
TITLE: ILLUMINATOR

PUBN-DATE: May 31, 1990

INVENTOR-INFORMATION:

| NAME | COUNTRY |
|--------------------|---------|
| YAMASHITA, HIROSHI | JP |
| FUJII, KANENAGA | JP |
| HAYAKAWA, JUNJI | JP |
| KOMIYAMA, TORU | JP |
| KOIZUMI, SHUN | JP |

ASSIGNEE-INFORMATION:

| NAME | COUNTRY |
|-------------------|---------|
| YAMASHITA HIROSHI | JP |
| FUJII KANENAGA | JP |
| HAYAKAWA JUNJI | JP |
| KOMIYAMA TORU | JP |
| KOIZUMI SHUN | JP |

APPL-NO: JP08500081
APPL-DATE: February 22, 1985

PRIORITY-DATA: JP08500081W (February 22, 1985)
INT-CL (IPC): G02B006/00
EUR-CL (EPC): F21V008/00

ABSTRACT:

The **illuminator** according to this invention consists of a rod adapted to transmit the **light** entering one end thereof to the other end, diffusion stripes, which are formed on the outer circumferential surface of the rod so that the diffusion layer extends continuously or intermittently in the axial direction of the rod, and which are composed of particulate bodies of a high refractive index, a transparent protective cylinder covering the outer circumferential surface of the rod with a clearance left between surface of the rod with a clearance left between the same outer circumferential surface and the inner circumferential surface of the protective cylinder, and a **sealing** member for sealing both ends of the circumferential clearance between the rod and protective cylinder. The light transmitted from one end to the other is sent out in the direction in which the light crosses the axis of the rod, by the diffusion-reflecting effect of the diffusion stripes and owing to the functions of the rod as a lens so as to make the light function as the illuminating light. This light is not accompanied by heat, nor does it require consideration for electric wiring and electric insulation. Accordingly, the light is suitable for the illumination of a refrigerating showcase and the operation of a lighted advertisement.